

Rite Way F-5 & F-7 Land Roller Specifications



Model	# of segments	Drum diameter	Drum thickness	Working width	Transport width	Transport length	Weight*	Frame	Tires
F5-46	5	41" to 42"	.53" to .60"	46'	13 ½'	45'	23,000 lbs.	6" x 4" x .25" wall	main - 12.5L x 15-12 ply rear - 11L- 15-8 ply
F5-50	5	41" to 42"	.53" to .60"	50'	13 ½'	47'	24,800 lbs.	6" x 4" x .25" wall	main - 12.5L x 15-12 ply rear - 11L- 15-8 ply
F5-58	5	41" to 42"	.53" to .60"	58'	13 ½'	51'	28,478 lbs.	6" x 4" x .25" wall	main - 12.5L x 15-12 ply rear - 11L- 15-8 ply
F5-62	5	41" to 42"	.53" to .60"	62'	13 ½'	53'	30,250 lbs.	6" x 4" x .25" wall	main - 12.5L x 15-12 ply rear - 11L x 15-8 ply
F5-68	5	41" to 42"	.53" to .60"	66'	13 ½'	55'	32,620 lbs.	6" x 4" x .25" wall	main - 12.5L x 15-12 ply rear - 11L x 15-8 ply
F7-65	7	41" to 42"	.53" to .60"	65'	13 ½'	54'	32,500 lbs.	6" x 4" x .25" wall	12.5L x 15-12 ply
F7-69	7	41" to 42"	.53" to .60"	69'	13 ½'	56'	33,740 lbs.	6" x 4" x .25" wall	12.5L x 15-12 ply
F7-81	7	41" to 42"	.53" to .60"	81'	13 ½'	62'	38,718 lbs.	6" x 4" x .25" wall	12.5L x 15-12 ply
F7-85	7	41 to 42"	.53" to .60"	85'	13 ½'	64'	39,950 lbs.	6" x 4" x .25' wall	12.5L x 15-12 ply

All Rite Way Land Rollers come equipped with *FORWARD*TM Unfolding System. Optional equipment: Acre Meter. *Weights are approximate

We are continuously improving our products. Design, specifications and material are subject to change without notice.