

**RITEWAY** 

**SINGLE LAND  
ROLLER SERIES**

**F1-20**

**FIXED HITCH**

SINGLE LAND ROLLER SERIES



**RITEWAY** 



## F1-20 LAND ROLLER

# SWING INTO SMOOTH.

Harvest your crops worry free. Promote even germination. Crush crop residue.

The 1-section roller applies uniform weight and surface contact across your fields, pushing rocks into the ground and leveling out clumps, firming your seedbed, and crushing hard-to-manage crop residues. The resulting smooth surface provides even germination, faster spraying, robust crops, and a trouble-free harvest.

## FIXED HITCH ROLLER



### 1 - Large Diameter Drums

A large 42" drum provides an ideal combination of weight and size to smooth the field without compaction.

### 2 - Telescopic Hydraulic Swing Hitch

Hydraulics allow you to switch from field to narrow transport mode without leaving your tractor, while the telescoping hitch allows for easy leveling of the unit.

### 3 - Replaceable Shaft

Discover easy maintenance with our replaceable drum spindles.

### 4 - Less Horsepower Required (per foot)

The 42" drum offers less rolling resistance.

### 5 - 2 - 7/16" Bearings

Heavy duty bearing ensure shock absorption when pushing rocks into the ground.

### 6 - Transport Lights

## HYDRAULIC SWING HITCH



## FIXED HITCH



### 1 - Large Diameter Drums

The same large diameter drums as the swing hitch (42") provide the idea weight to smooth your fields.

Drum Thickness: 1/2"

### 2 - Replaceable Shaft

Discover easy maintenance with our replaceable drum spindles.

### 3 - 2 - 7/16" Bearings

Heavy duty bearing ensure shock absorption when pushing rocks into the ground.

### 4 - Easy Transport

The transport width is only 1' (30 cm) wider than the model size you choose.

### 5 - Transport Lights





# MADE TO WORK. BUILT TO LAST.

## SPECIFICATIONS:

<b>F1-20</b>						
WORKING WIDTH	WEIGHT	DRUM DIAMETER	TRANSPORT CLEARANCE	TRANSPORT WIDTH	TRANSPORT LENGTH	TIRES
20' (6.1 M)	7,600 lbs (3,447 kg)	42" (107 cm)	16" (41 cm)	8' (2.4 M)	27' (8.2 M)	12.5 L X 15-12 PLY

<b>FIXED-HITCH</b>						
MODEL	WEIGHT	DRUM DIAMETER	WING CONFIGURATION	TRANSPORT WIDTH	TRANSPORT LENGTH	TIRES
FH-12	5,000 lbs (2,268 kg)	42" (107 cm)	12' (3.8 m)	13' (4.1 m)	13' 11" (4.2 m)	11 L x 15 - 8 PLY
FH-14	5,500 lbs (2,485 kg)	42" (107 cm)	14' (4.3 m)	15' (4.6 m)	13' 11" (4.2 m)	11 L x 15 - 8 PLY
FH-16	6,000 lbs (2,722 kg)	42" (107 cm)	16' (4.9 m)	17' (5.2 m)	13' 11" (4.2 m)	11 L x 15 - 8 PLY
FH-18	6,500 lbs (2,948 kg)	42" (107 cm)	18' (5.5 m)	19' (5.8 m)	13' 11" (4.2 m)	11 L x 15 - 8 PLY
FH-20	7,000 lbs (3,175 kg)	42" (107 cm)	20' (6.1 m)	21' (6.4 m)	13' 11" (4.2 m)	12.5 L x 15-12 PLY



We are continuously improving our products. Design, specifications, and material are subject to change without notice.

For more information on the 1-section Rollers or other land improvement equipment, visit your local Rite Way equipment dealer or [www.RiteWayMfg.com](http://www.RiteWayMfg.com). Toll free: 1-800-352-8822

