

# F-1 LAND ROLLER SPECIFICATIONS



Model	# of Segments	Drum Diameter	Drum Thickness*	Wing Configuration	Transport Width	Transport Length	Weight*	Frame	Tires
F1-20 HS	1	42" / 107cm	0.53" (1.3cm)	20' 6.1m	8' / 2.4m	27' / 8.2m	7,600 lbs / 3,447 kg	shaft: 2.44" / 6.2cm	12L x 15-12 ply
FH-12 or TPH-12	1	42" / 107cm	0.53" (1.3cm)	12' 3.8m	13' / 4.1m	FH: 13' 11" / 4.2m TPH: 60" / 152cm	5,000 lbs / 2 268 kg	shaft: 2.44" / 6.2cm	11L x 15 - 12 ply
FH-14 or TPH-14	1	42" / 107cm	0.53" (1.3cm)	14' 4.3m	15' / 4.6m	FH: 13'11" / 4.2m TPH: 60" / 152cm	5,500 lbs / 2 485 kg	shaft: 2.44" / 6.2cm	11L x 15 - 12 ply
FH-16 or TPH-16	1	42" / 107cm	0.53" (1.3cm)	16' 4.9m	17' / 5.2m	FH: 13' 11" / 4.2m TPH: 60" / 152cm	6,000 lbs / 2 722 kg	shaft: 2.44" / 6.2cm	11L x 15 - 12 ply
FH-18 or TPH-18	1	42" / 107cm	0.53" (1.3cm)	18' 5.5m	19' / 5.8m	FH: 13' 11" / 4.2m TPH: 60" / 152cm	6,500 lbs / 2 948 kg	shaft: 2.44" / 6.2cm	11L x 15 - 12 ply
FH-20 or TPH-20	1	42" / 107cm	0.53" (1.3cm)	20' 6.1m	21' / 6.4m	FH: 13' 11" / 4.2m TPH: 60" / 152cm	7,000 lbs / 3 175 kg	shaft: 2.44" / 6.2cm	11L x 15 - 12 ply

\*approximate

We are continuously improving our products. Design, specifications and material are subject to change without notice.